AltoLink 5GHz 5P624

Outdoor Long Range Point-to-Point Radio Unit

The 5P624 is a point-to-point radio operating in 4.9-6GHz with integrated 24dBi antenna that provides a connectivity option where longer range is required.

The 5P624 is carrier-grade and features IP67 weather-sealing for reliable operation outdoors and in harsh environments.



High Capacity

Up to 1.2Gbps aggregate

Low Latency

<2.5ms average latency

Adjustable TDD Symmetry

Configurable downlink/uplink ratio options: 50/50, 25/75 and 75/25

Integrated Antenna

Integrated 24dBi panel antenna with dual linear polarization and low side lobe levels for improved interference mitigation

Well Connected

Built-in 2.5GbE RJ45 and 1GbE SFP ports

Long Range

Full capacity range up to 2km

Security

AES 256 encryption with automatic secure key distribution

Carrier-Grade

IP67 rated enclosure for reliable, long-term operation in the field



Specifications

SYSTEM

Configuration Point-to-Point

Frequency

Range 4.90 – 6.06GHz (subject to local

regulations)

Duplexing TDD

Modulation OFDM - BPSK, QPSK, 16QAM, 64QAM,

256QAM, 1024QAM, 4096QAM

Antenna Integrated, 24dBi, panel antenna with

dual linear polarization 3dB azimuth beamwidth: 9° 3dB elev. beamwidth: 9°

Maximum Output

Power to Antenna 26dBm per chain (subject to local

regulation)

Antenna Modes MIMO 2x2, adaptive spatial

multiplexing/diversity

Full Capacity

Range Up to 2km

Capacity Up to 1.2 Gbps aggregate on 80 MHz

channel

Ethernet

Frame Type Transparent bridging of all Ethernet

types including VLAN

VLAN Support 802.1Q

Latency <2.5ms average

L2 Bridge Supported Security AES 256

MECHANICAL

Dimensions

(**H x W x D**) 14.7" x 14.6" x 3.9" (373 x 370 x 98mm)

Weight 5.7 lbs (2.6 Kg)

Operating

Temperature -40° to +55°C

Ingress Protection IP67 **Regulatory** FCC, IC

Safety UL/CSA-C22.2 62368-1, UL/CSA-C22.2

60950-22

EMC USA: FCC 47CFR Part 15 Subpart B,

Class B

Canada: ICES-003, CISPR 32 Class B

CONNECTIVITY

Ethernet 1 x 2.5GbE RJ45

 SFP
 1 x 1Gbps

 Voltage
 42.5-57VDC

 PoE input
 802.3at

Power

Consumption 30W maximum

MANAGEMENT

Management Web GUI, and SNMP (v1, v3)

